

MF TW SERIES

Trailed Round Baler Wrappers





Straight forward, easy to use bale wrappers with a technically advanced and reliable design.

- Low Position Wrapping Table
- Reduced Film Consumption
- Quick Lock System
- Gentle Bale Discharge
- Strong Welded Loading Arm
- Bale Tipper
- Tighter Wrapping
- E-Link Terminal

Specifications

| | TW 130 | TW 160 |
|------------------------------|--|-----------|
| Transport width | 2.53 m | 2.28 m |
| Transport length | 4.70 m | 5.80 m |
| Transport height | 2.30 m) | 2.70 m |
| Maximum bale diameter | 0.90 - 1.30 m | 1.60 m |
| Maximum bale width | 1.25 m | 1.50 m |
| Maximum bale weight | 1000 kg | 1200 kg |
| Tyre size | 10.0/75x15.3 | 380/55x17 |
| Linkage | Pin hitch | |
| Hydraulic connections | 1 Single acting valve with free return | |
| Hydraulic flow | 30 litre/min at 150 bar | |
| Maximum speed wrapping table | 30 rpm | |
| Maximum speed | 40 km/h | |
| Power requirement | 40hp | 54hp |
| Approximate weight | 1080 kg | 2080 kg |
| Film stretch | 55 % / 70 % | |

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.







facebook.com/MasseyFergusonGlobal twitter.com/AGCOcorp youtube.com/MasseyFergusonVideo masseyferguson.com.au



